

Granville EP 75W/90 Semi-Synthetic

1 Litre, 5 Litre, 20 Litre & 205 Litre

PRODUCT DESCRIPTION

Granville EP 75W/90 is a semi synthetic, heavy duty, multipurpose gear oil manufactured from high quality synthetic base oils and additives to provide a gear oil suitable for today's modern gearboxes. EP 75W/90 has outstanding load carrying capacity which is essential for shock/load, high/torque and high/speed service operation.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-5
MIL-L-2105 D



* Image for illustrative purposes only.

PRODUCT BENEFITS

- * Reduced fuel consumption
- * Outstanding wear protection
- * Smoother gear shift
- * Long service life

PRODUCT USAGE

For manual transmissions and axles where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the vehicle manufacturer.

STORAGE INSTRUCTIONS

Store upright and sealed in a cool, dry place out of the reach of children

SIZE	PART NO	BARCODE
1 Litre	0011	5020618000112
5 Litre	0012	5020618000129
20 Litre	0084	5020618000846
205 Litre	1700	5020618017004



Granville EP 75W/90 Semi-Synthetic

1 Litre, 5 Litre, 20 Litre & 205 Litre

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	13.5	<18.5	15.932
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			107.44
Density	ASTM D792	@ 15°C			0.876

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

